product details **64570**

Product description: 64570
Product code: 4050300014098
Quantity: Folding carton box (FS) contains 1 Piece (PCE)

You can find this product in the eCatalog:
http://catalog.myosram.com?~language=EN&~country=US&it_p=4050300014098

Applications	
Burning position	horizontal

General Description	
Base (standard designation)	R7s

Logistical Data	
Product weight	10 g

Technical - Electrical Data	
Construction wattage	800 W
Construction voltage	230 V
Lamp voltage	230 V
Nominal voltage	220-230 V

Technical - Geometries	
Diameter	15 mm
Filament length	25.00 mm
Length	74.90 mm

Technical - Lifespan	
Lifespan	15 h

Technical - Light Technical Data	
Luminous flux	22000 lm
Color temperature	3400 K

Packaging units

Product code	Packaging type and content	Dimensions in h x w x l	Gross weight	Volume
4050300014098	Folding carton box contains 1 Piece	33.000 mm x 33.000 mm x 113.000 mm	20.000 g (0.000 g)	0.123 Cubic dec.
4050300206868	Shipping carton box contains 25 Piece	180.000 mm x 130.000 mm x 180.000 mm	611.000 g (0.000 g)	4.212 Cubic dec.

From their designs, halogen mains voltage lamps can be categorized as single-ended and double-ended lamps. Depending on the application, they are designed to operate on 230 V, 240 V or 120 V.
The color temperature of the lamps varies according to the application: 3,400 K for maximum luminous efficacy, 3,200 K for professional film and TV work, 3,000 K or 2,900 K for applications where long life is important.

Safety

To prevent personal injury or damage to property, halogen lamps may only be operated in suitable luminairesdesigned with suitable mechanisms (protective shields, grids, etc.) to ensure that in the event of a lamp bursting no parts/shards can escape and that during operation no ultraviolet radiation can escape. There must also be a warning sign to indicate that the lamps give off high levels of heat. Detailed information is available on request.

Subject to change without notice. Errors and omission excepted.
© 2011 OSRAM GmbH